

PRODUCT ID: 54871

Outdoor Blank-out LED Backlit Sign

MODEL

PHX1434GRG-N883/120-277VAC



DIMENSIONS

14" H x 34" W x 2.5" D (est. 15.388 lbs)

CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Black opaque

Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
LANE OPEN	Green Wide Angle LED	2.25"	0.260-0.113
LANE CLOSED	Red Wide Angle LED	2.25"	0.116-0.050
24-HOUR ATM	Green Wide Angle LED	2.25"	0.260-0.113

NOTE: Above messages are independently controlled.

Signal-Tech

4985 Pittsburgh Ave.

Erie, PA 16509

Phone: (877) 547-9900

Fax: (814) 835-2300

Email: sales@signal-tech.com

Website: www.signal-tech.com



Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



2 1/2 in

Sample Display Options

LANE OPEN

LANE CLOSED

24-HOUR ATM

Frame Detail

