

## PRODUCT ID: 39382

### Outdoor LED Backlit Sign

#### MODEL

PHXF718W-125B/120-277VAC



#### DIMENSIONS

7" H x 18" W x 2.5" D (est. 4.084 lbs)

#### CLASS

CLASS: PHXF Series

Control Method: Switch (not included) or external relay.

#### CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, impact modified acrylic (0000)

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

#### ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

#### MESSAGE

Color: Blue translucent


Font: Other: (Optima)

Illumination: White high intensity LED backlit. Message always visible.

Sign Messages: See message table below

## Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



MESSAGE	LED/COLOR	HEIGHT	AMPS
---------	-----------	--------	------

ATM	White Wide Angle LED	4.75"	0.195-0.084
-----	----------------------	-------	-------------

NOTE: Above messages are independently controlled.

#### Signal-Tech

4985 Pittsburgh Ave.

Erie, PA 16509

Phone: (877) 547-9900

Fax: (814) 835-2300

Email: sales@signal-tech.com

Website: www.signal-tech.com



#### Frame Detail

