

PRODUCT ID: 67951
DOT LED Blank-Out Sign

MODEL
 DOT4129RW-D602/9-24VDC



DIMENSIONS
 41" H x 29" W x 6.5" D (est. 74.221 lbs)

CLASS
 Class: DOT Series
 Control Method: Switch (not included) or external relay.

CONSTRUCTION
 Cabinet: Extruded aluminum cabinet with welded seams, NEMA 4X rated/IP66.
 Hinged door with silicone gasket, tool-less stainless-steel latches. 6.5" Deep.
 Face Material: 1/8" impact resistant, smoke-tinted polycarbonate (5109)
 Faces: Single Faced Sign
 Finish: Powdercoat Black

ELECTRICAL
 Input Voltage: 9-24 VDC
 Photodimming: IR photocells for auto photodimming
 Power Supplies: No Redundancy
 UL/cUL Listed: Listed for wet locations

MESSAGE
 Illumination: Super bright direct view LEDs. Message blanks out when off.
 Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
NO RIGHT TURN SYMBOL W/ TRAIN	Red, White Narrow Angle	20.75", 12.625", 6.0"	11.911-4.467


NOTE: Above messages are independently controlled.

Signal-Tech
 4985 Pittsburgh Ave.
 Erie, PA 16509
 Phone: (877) 547-9900
 Fax: (814) 835-2300
 Email: sales@signal-tech.com
 Website: www.signal-tech.com



Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

