PRODUCT ID: 13240

Outdoor Blank-out LED Direct-view Sign

MODEL

TCL1442GGGRGR-K040/120-277VAC

DIMENSIONS

14" H x 42" W x 2.5" D (est. 17.793 lbs)

CLASS

CLASS: TCL Series
Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back
Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.
Face Material: 1/8" impact resistant, smoke-tinted acrylic (5109)
Faces: Single Faced Sign
Finish: Duranodic Bronze
Mounting Channel: None

ELECTRICAL

Flashing: Not Included
Input Voltage: 120-277 VAC
Photodimming: None
UL/cUL Listed: Listed for wet locations

MESSAGE

Illumination: Super bright direct view LEDs. Message blanks out when off.
Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
ATM	Green Wide Angle LED	3.5"	0.039-0.017
OPEN TOP	Green Wide Angle LED	3.5"	0.055-0.024
CLOSED TOP	Red Wide Angle LED	3.5"	0.041-0.018
DRIVE UP	Green Wide Angle LED	3.5"	0.081-0.035
OPEN BOT	Green Wide Angle LED	3.5"	0.055-0.024
CLOSED BOT	Red Wide Angle LED	3.5"	0.041-0.018

NOTE: Above messages are independently controlled.

Signal-Tech
4985 Pittsburgh Ave.
Erie, PA 16509
Phone: (877) 547-9900
Fax: (814) 835-2300
Email: sales@signal-tech.com
Website: www.signal-tech.com

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

Sample Display Options

Frame Detail



Copyright (C) 2024 Signal-Tech