

Direct-View LED Traffic Controller TCL6024GR-C4030

PRODUCT NUMBER

11530



CABINET DIMENSIONS

60" H x 24" W x 5.5" D

ILLUMINATION SOURCE

Super bright, wide viewing angle LEDs
Available in green, red, blue, amber, and white LEDs
Messages "blankout" when turned off, eliminating confusion
Long life, solid state lighting

ELECTRICAL

Integrated solid state power supply
Standard Voltage: 120 VAC, Optional Voltages: 9-36 V, 240 VAC, 277 VAC
Maximum amps per lighted message (at 120 V) shown in the table below
UL/CUL approved for wet locations
120V AC; Optional voltages 12V DC, 24V DC, 240V AC, 277V AC
1backlit board, 0.48 amps maximum

CONSTRUCTION

Faces: Single Faced Sign
Extrusions: 5.5" deep mitered corrosion resistant aluminum housing with integrated hinged face.
Face Material: 1/8" routed aluminum panel backed with Impact Resistant, white lexan 1/8" thick face.
Vinyl Style: Vinyl is applied in a standard stencil cut style
Vinyl Color: Applied vinyl color is translucent Orange

FINISH

Standard Cabinet Color: Duranodic Bronze
Custom colors available upon request

MESSAGE	COLOR	HEIGHT	AMPS
6 w/symbols Orange	Orange Translucent Vinyl	7", 3.5"	0.48
OPEN	Green Wide Angle Oval	3.5"	0.03
CLOSED	Red Wide Angle Oval	3.5"	0.03

Signal-Tech
4985 Pittsburgh Ave.
Erie, PA 16509
Phone: (877) 547-9900
Fax: (814) 835-2300
Email: sales@signal-tech.com
Website: www.signal-tech.com



Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

