PRODUCT ID: 39484

Outdoor LED Backlit Sign

MODEL

PHXF734W-552R/120-277VAC



DIMENSIONS

7" H x 34" W x 2.5" D (est. 6.728 lbs)

CLASS

CLASS: PHXF Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, impact modified acrylic (0000)

Faces: Single Faced Sign Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface Mounting Channel: None

ELECTRICAL

Flashing: Not Included Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Red translucent Font: Swiss 721 Bold BT

Illumination: White high intensity LED backlit. Message always visible.

Sign Messages: See message table below

MESSAGE LED/COLOR | HEIGHT | AMPS

Drive-Up ATM White Wide Angle LED 4.0"

NOTE: Above messages are independently controlled.

Signal-Tech

4985 Pittsburgh Ave. Erie. PA 16509 Phone: (877) 547-9900

Fax: (814) 835-2300 Email: sales@signal-tech.com Website: www.signal-tech.com



08262021 | DP

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

Drive-Up ATM

Frame Detail



Copyright (C) 2025 Signal-Tech