

Direct-View LED Traffic Controller TCL714RG-225H

PRODUCT NUMBER

7383

CABINET DIMENSIONS

7" H x 14" W x 2.5" D

ILLUMINATION SOURCE

Super bright, wide viewing angle LEDs
Available in green, red, blue, amber, and white LEDs
Messages "blankout" when turned off, eliminating confusion
Long life, up to 100,000+ hours

ELECTRICAL

Integrated solid state power supply
Standard Voltage: 120 VAC, Optional Voltages: 9-36 V, 240 VAC, 277 VAC
Maximum amps per lighted message (at 120 V) shown in the table below
UL/CUL approved for wet locations

CONSTRUCTION

Faces: Single Faced Sign
Extrusions (TCL): Slim line continuous, corrosion resistant, aluminum housing 2.5" deep
Face Material: Impact Resistant, Red Polycarbonate 1/8" thick, Green Polycarbonate 1/8" thick.


FINISH

Standard Cabinet Color: Duranodic Bronze
Custom colors available upon request




Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



MESSAGE	COLOR	HEIGHT	AMPS
RED INDICATOR DOT	Red Wide Angle Oval	5.0"	0.01
GREEN INDICATOR DOT	Green Wide Angle Oval	5.0"	0.01



Signal-Tech
4985 Pittsburgh Ave.
Erie, PA 16509
Phone: (877) 547-9900
Fax: (814) 835-2300
Email: sales@signal-tech.com
Website: www.signal-tech.com



Proudly Made in the USA