PRODUCT ID: 11807

Outdoor Blank-out LED Direct-view Sign

MODEL TCL1434GGRGGR-B808/120-277VAC



DIMENSIONS 14" H x 34" W x 2.5" D (est. 12.824 lbs)

CLASS

CLASS: TCL Series Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: 1/8" impact resistant, smoke-tinted polycarbonate (5109) Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None

ELECTRICAL

Flashing: Not Included Input Voltage: 120-277 VAC Photodimming: None UL/cUL Listed: Listed for wet locations

MESSAGE

Illumination: Super bright direct view LEDs. Message blanks out when off. Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
DRIVE-UP	Green Wide Angle LED	2.75"	0.077-0.034
OPEN	Green Wide Angle LED	3.5"	0.055-0.024
	Red Wide Angle LED		0.041-0.018
ATM	Green Wide Angle LED	3.5"	0.039-0.017
OPEN	Green Wide Angle LED	3.5"	0.055-0.024
CLOSED	Red Wide Angle LED	3.5"	0.041-0.018
NOTE: Above messages are independently controlled			

NOTE: Above messages are independently controlled.

Signal-Tech 4985 Pittsburgh Ave. Erie, PA 16509 Phone: (877) 547-9900 Fax: (814) 835-2300 Email: sales@signal-tech.com Website: www.signal-tech.com



Copyright (C) 2024 Signal-Tech

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Sample Display Options



07122022 | DP