PRODUCT ID: 12891

Outdoor Blank-out LED Direct-view Sign

MODEL

TCL1442GGGR-C837/120-277VAC



DIMENSIONS

14" H x 42" W x 2.5" D (est. 14.673 lbs)

CLASS

CLASS: TCL Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: 1/8" impact resistant, smoke-tinted polycarbonate (5109)

Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None

ELECTRICAL

Flashing: Not Included Input Voltage: 120-277 VAC Photodimming: None
UL/cUL Listed: Listed for wet locations

MESSAGE

Illumination: Super bright direct view LEDs. Message blanks out when off.

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
NIGHT DEPOSIT/ATM	Green Wide Angle LED	2.75"	0.183-0.079
COMMERCIAL	Green Wide Angle LED	2.75"	0.120-0.052
OPEN	Green Wide Angle LED	3.5"	0.055-0.024
CLOSED	Red Wide Angle LED	3.5"	0.041-0.018

NOTE: Above messages are independently controlled.

Signal-Tech

4985 Pittsburgh Ave. Erie, PA 16509

Phone: (877) 547-9900 Fax: (814) 835-2300

Email: sales@signal-tech.com Website: www.signal-tech.com



Product View


NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Sample Display Options







Copyright (C) 2024 Signal-Tech