

PRODUCT ID: 13006
Outdoor Blank-out LED Direct-view Sign

MODEL
TCL1442GGGR-C886/120-277VAC



DIMENSIONS
14" H x 42" W x 2.5" D (est. 17.719 lbs)

CLASS
CLASS: TCL Series
Control Method: Switch (not included) or external relay.

CONSTRUCTION
Back Construction: 0.050" Lift-n-Shift Back
Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.
Face Material: 1/8" impact resistant, smoke-tinted acrylic (5109)
Faces: Single Faced Sign
Finish: Duranodic Bronze
Mounting Channel: None

ELECTRICAL
Flashing: Not Included
Input Voltage: 120-277 VAC
Photodimming: None
UL/cUL Listed: Listed for wet locations

MESSAGE
Illumination: Super bright direct view LEDs. Message blanks out when off.
Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
ATM/NIGHT DROP	Green Wide Angle LEDs	3.5"	0.156-0.068
TELLER	Green Wide Angle LEDs	3.5"	0.065-0.028
OPEN	Green Wide Angle LEDs	3.5"	0.055-0.024
CLOSED	Red Wide Angle LEDs	3.5"	0.041-0.018

NOTE: Above messages are independently controlled.

Signal-Tech
4985 Pittsburgh Ave.
Erie, PA 16509
Phone: (877) 547-9900
Fax: (814) 835-2300
Email: sales@signal-tech.com
Website: www.signal-tech.com



Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Sample Display Options



Frame Detail

