Product View PRODUCT ID: 23889 NOTE: Sign image may not exactly represent the finished product. For illustration purposes only. Outdoor Blank-out LED Direct-view Sign Sample Display Options MODEL TCL347GR-F169/120-277VAC DIMENSIONS 34" H x 7" W x 2.5" D (est. 9.995 lbs) CLASS CLASS: TCL Series Control Method: Switch (not included) or external relay. CONSTRUCTION Back Construction: 0.050" Lift-n-Shift Back Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: 1/8" impact resistant, smoke-tinted polycarbonate (5109) Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None **ELECTRICAL** Flashing: Not Included Input Voltage: 120-277 VAC Photodimming: None UL/cUL Listed: Listed for wet locations MESSAGE 34" Illumination: Super bright direct view LEDs. Message blanks out when off. Sign Messages: See message table below MESSAGE LED/COLOR |HEIGHT|AMPS OPEN w/ Left Down Arrow Green Wide Angle LEDs 3.5" 0.067-0.029 CLOSED w/ Left Down Arrow Red Wide Angle LEDs 3.5" 0.051-0.022 Frame Detail NOTE: Above messages are independently controlled. Signal-Tech 4985 Pittsburgh Ave. Signal-Tech Erie, PA 16509 Phone: (877) 547-9900 Fax: (814) 835-2300 Email: sales@signal-tech.com 2.5" — 7" Website: www.signal-tech.com

Copyright (C) 2024 Signal-Tech

11032020 | DP