PRODUCT ID: 26032

Outdoor Blank-out LED Backlit Sign

MODEL

PHX734GR-220/120-277VAC



DIMENSIONS

7" H x 34" W x 2.5" D (est. 7.182 lbs)

CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface Mounting Channel: None

ELECTRICAL

Flashing: Not Included Input Voltage: 120-277 VAC
UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Black opaque Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
OPEN	Green Wide Angle LED	3.75"	0.173-0.075
FULL	Red Wide Angle LED	3.75"	0.116-0.050

NOTE: Above messages are independently controlled.

Signal-Tech

4985 Pittsburgh Ave. Erie. PA 16509 Phone: (877) 547-9900

Fax: (814) 835-2300

Email: sales@signal-tech.com Website: www.signal-tech.com



Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Sample Display Options



