PRODUCT ID: 27239

DOT LED Blank-Out Sign

MODEL

DOT3024RW-D601/100-240VAC



DIMENSIONS

30" H x 24" W x 5" D (est. 47.431 lbs)

CLASS

Class: DOT Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Cabinet: Extruded aluminum cabinet with welded seams, NEMA 4X rated/IP66. Hinged door with 1" silicone gasket, tool-less stainless-steel latches. 5.0" Deep. Face Material: Replaceable 1/4" thick, dark grey polycarbonate (I35)

Faces: Single Faced Sign

Finish: Powdercoat Black
Integral Hood: Optional hood available
Mounting Channel: None

ELECTRICAL
Input Voltage: 100-240 VAC
Photodimming: (3) Redundant fail-safe photocells for auto photodimming

Power Supplies: Redundant

UL/cUL Listed: Listed for wet locations

MESSAGE

Illumination: Super bright direct view LEDs. Message blanks out when off. Sign Messages: See message table below

MESSAGE LED/COLOR | HEIGHT | AMPS

No Left Turn Symbol w/TRAIN Red. White Narrow Angle LED | 15.5", 10.0", 4.5" | 0.309-0.129

NOTE: Above messages are independently controlled.

Signal-Tech

4985 Pittsburgh Ave. Erie. PA 16509 Phone: (877) 547-9900

Fax: (814) 835-2300

Email: sales@signal-tech.com Website: www.signal-tech.com



Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

