## PRODUCT ID: 29242

Outdoor Blank-out LED Direct-view Sign

#### **MODEL**

TCL2118GGR-H393/120-277VAC



### **DIMENSIONS**

21" H x 18" W x 2.5" D (est. 9.673 lbs)

### **CLASS**

CLASS: TCL Series

Control Method: Switch (not included) or external relay.

#### **CONSTRUCTION**

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: 1/8" impact resistant, smoke-tinted polycarbonate (5109)

Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None

#### **ELECTRICAL**

Flashing: Not Included Input Voltage: 120-277 VAC Photodimming: None UL/cUL Listed: Listed for wet locations

#### **MESSAGE**

Illumination: Super bright direct view LEDs. Message blanks out when off.

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	<b>AMPS</b>
ATM	Green Wide Angle LED	3.5"	0.045-0.020
OPEN Down right Arrow	Green Wide Angle LED	3.5", 4.0"	0.075-0.032
CLOSED Down right Arrow	Red Wide Angle LED	3.5", 4.0"	0.051-0.022

NOTE: Above messages are independently controlled.

#### Signal-Tech


4985 Pittsburgh Ave. Erie, PA 16509 Phone: (877) 547-9900

Fax: (814) 835-2300 Email: sales@signal-tech.com Website: www.signal-tech.com



# **Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



## Sample Display Options









Copyright (C) 2024 Signal-Tech

05102021 | DP