## **Product View PRODUCT ID: 31695** NOTE: Sign image may not exactly represent the finished product. For illustration purposes only. Outdoor Blank-out LED Direct-view Sign MODEL TCL77A-224H/12-24VDC DIMENSIONS 7" H x 7" W x 2.5" D (est. 3.275 lbs) CLASS CLASS: TCL Series Control Method: Switch (not included) or external relay. CONSTRUCTION Back Construction: 0.050" Lift-n-Shift Back Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: Injection molded, impact resistant Lexan hood with Lexan lenses Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None - 3 in · **ELECTRICAL** Flashing: Factory setting 55fpm. Input Voltage: 12-24 VDC Photodimming: None UL/cUL Listed: Listed for wet locations MESSAGE Illumination: Super bright direct view LEDs. Message blanks out when off. 7 in Sign Messages: See message table below LED/COLOR | HEIGHT | AMPS MESSAGE Indicator Dot Amber Wide Angle LED 4.0" 0.333-0.167 Indicator Dot (Flashing) Amber Wide Angle LED 0.333-0.167 4.0" 2 1/2 in → 7 in Frame Detail NOTE: Above messages are independently controlled. Signal-Tech 4985 Pittsburgh Ave. Signal-Tech Erie, PA 16509 Phone: (877) 547-9900 Fax: (814) 835-2300 Email: sales@signal-tech.com Website: www.signal-tech.com 01112021 | DP Copyright (C) 2024 Signal-Tech