

PRODUCT ID: 34528
Outdoor Blank-out LED Backlit Sign

MODEL
PHX734GR-A183/120-277VAC



DIMENSIONS
7" H x 34" W x 2.5" D (est. 6.476 lbs)

CLASS
Class: PHX Series
Control Method: Switch (not included) or external relay.

CONSTRUCTION
Back Construction: 0.050" Lift-n-Shift Back
Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.
Face Material: 1/8" thick, dark grey diffused acrylic
Faces: Single Faced Sign
Finish: Duranodic Bronze
Graphic: Printed graphic applied to surface
Mounting Channel: None

ELECTRICAL
Flashing: Not Included
Input Voltage: 120-277 VAC
UL/cUL Listed: Listed for wet locations

MESSAGE
Color: Black opaque
Font: Swiss 721 Bold BT
Illumination: Backlit with high intensity LEDs. Message blanks out when off
Sign Messages: See message table below

| MESSAGE | LED/COLOR | HEIGHT | AMPS |
|-------------------|----------------------|--------|-------------|
| PARK w/Left Arrow | Green Wide Angle LED | 3.0" | 0.173-0.075 |
| EXIT w/Up Arrow | Red Wide Angle LED | 3.5" | 0.116-0.050 |


NOTE: Above messages are independently controlled.

Signal-Tech
4985 Pittsburgh Ave.
Erie, PA 16509
Phone: (877) 547-9900
Fax: (814) 835-2300
Email: sales@signal-tech.com
Website: www.signal-tech.com



Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Sample Display Options



Frame Detail

