## PRODUCT ID: 37697

Outdoor Blank-out LED Backlit Sign

#### MODEL

PHX734W-F520R/120-277VAC



#### DIMENSIONS

7" H x 34" W x 2.5" D (est. 6.435 lbs)

#### **CLASS**

Class: PHX Series

Control Method: Switch (not included) or external relay.

#### CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface Mounting Channel: None

#### **ELECTRICAL**

Flashing: Not Included Input Voltage: 120-277 VAC
UL/cUL Listed: Listed for wet locations

### **MESSAGE**

Color: Black opaque Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

#### **MESSAGE** LED/COLOR | HEIGHT | AMPS

Exit w/ Do Not Enter Symbols | Printed Red Translucent, White Wide Angle LED | 4.0", 3.75", 4.0" | 0.347-0.150

NOTE: Above messages are independently controlled.

#### Signal-Tech

4985 Pittsburgh Ave. Erie. PA 16509 Phone: (877) 547-9900

Fax: (814) 835-2300 Email: sales@signal-tech.com Website: www.signal-tech.com



# **Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

