PRODUCT ID: 38750

Indoor Blank-out LED Backlit Sign

MODEL

SBL1212R-195/120-277VAC



DIMENSIONS

12" H x 12" W x 2.5" D (est. 5.046 lbs)

CLASS

Class: SBL Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

ELECTRICAL

Flashing: Not Included Input Voltage: 120-277 VAC UL/cUL Listed: Listed

MESSAGE

Color: Black opaque Font: Swiss 721 Bold BT

Illumination: Backlit with LEDs. Message blanks out when off.

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
IN LISE	Red Wide Angle I FD	3.5"	0.065-0.028

NOTE: Above messages are independently controlled.

Signal-Tech

4985 Pittsburgh Ave. Erie, PA 16509 Phone: (877) 547-9900

Fax: (814) 835-2300 Email: sales@signal-tech.com



Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



