

PRODUCT ID: 38981

Outdoor Blank-out LED Backlit Sign

MODEL

PHX1442GGRGGR-300



DIMENSIONS

14" H x 42" W x 2.25" D (est. 9.095 lbs)

CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.25" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Mounting Channel:

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Black opaque

Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
ATM	Wide Angle Green Diffused	3.5"	0.413-0.179
OPEN	Wide Angle Green Diffused	3.5"	0.413-0.179
CLOSED	Wide Angle Red Diffused	3.5"	0.267-0.116
TELLER	Wide Angle Green Diffused	3.0"	0.413-0.179
OPEN	Wide Angle Green Diffused	3.5"	0.413-0.179
CLOSED	Wide Angle Red Diffused	3.5"	0.267-0.116

NOTE: Above messages are independently controlled.

Signal-Tech

4985 Pittsburgh Ave.

Erie, PA 16509

Phone: (877) 547-9900

Fax: (814) 835-2300

Email: sales@signal-tech.com

Website: www.signal-tech.com



Proudly Made in the USA

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

