

**PRODUCT ID: 39380**  
Outdoor LED Backlit Sign

**MODEL**  
PHXF1418W-H572R/120-277VAC



**DIMENSIONS**  
14" H x 18" W x 2.5" D (est. 7.519 lbs)

**CLASS**  
**CLASS:** PHXF Series  
**Control Method:** Switch (not included) or external relay.

**CONSTRUCTION**  
**Back Construction:** 0.050" Lift-n-Shift Back  
**Cabinet:** 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.  
**Face Material:** 1/8" thick, impact modified acrylic (0000)  
**Faces:** Single Faced Sign  
**Finish:** Duranodic Bronze  
**Graphic:** Printed graphic applied to surface  
**Mounting Channel:** None

**ELECTRICAL**  
**Flashing:** Not Included  
**Input Voltage:** 120-277 VAC  
**UL/cUL Listed:** Listed for wet locations

**MESSAGE**  
**Color:** Red translucent  
**Font:** Swiss 721 Bold BT  
**Illumination:** White high intensity LED backlit. Message always visible.  
**Sign Messages:** See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
STOP HERE ONE VEHICLE AT A TIME	Red Translucent	2.75", 2.25"	0.368-0.159

NOTE: Above messages are independently controlled.

**Signal-Tech**  
4985 Pittsburgh Ave.  
Erie, PA 16509  
Phone: (877) 547-9900  
Fax: (814) 835-2300  
Email: [sales@signal-tech.com](mailto:sales@signal-tech.com)  
Website: [www.signal-tech.com](http://www.signal-tech.com)



**Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

