

**PRODUCT ID: 43958**  
**DOT LED Blank-Out Sign**

**MODEL**  
DOT2424DRGRG-175/100-240VAC



**DIMENSIONS**  
24" H x 24" W x 11.5" D (est. 71.768 lbs)

**CLASS**  
Class: DOT Series  
Control Method: Switch (not included) or external relay.

**CONSTRUCTION**  
Cabinet: Extruded aluminum cabinet with welded seams, NEMA 4X rated/IP66. Two hinged doors with 1" silicone gasket, tool-less stainless-steel latches 11.5" Deep.  
Face Material: Replaceable 1/4" thick smoke-tinted polycarbonate (5109)  
Faces: Double Faced Sign  
Finish: Powdercoat Black  
Integral Hood: Optional hood available  
Mounting Channel: None

**ELECTRICAL**  
Input Voltage: 100-240 VAC  
Photodimming: (3) Redundant fail-safe photocells for auto photodimming  
Power Supplies: Redundant  
UL/cUL Listed: Listed for wet locations

**MESSAGE**  
Illumination: Super bright direct view LEDs. Message blanks out when off.  
Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
X	Red Narrow Angle LED	16.75"	0.187-0.078
Down Arrow	Green Narrow Angle LED	17.5"	0.222-0.093
X	Red Narrow Angle LED	16.75"	0.187-0.078
Down Arrow	Green Narrow Angle LED	17.5"	0.222-0.093



NOTE: Above messages are independently controlled.

**Signal-Tech**  
4985 Pittsburgh Ave.  
Erie, PA 16509  
Phone: (877) 547-9900  
Fax: (814) 835-2300  
Email: sales@signal-tech.com  
Website: www.signal-tech.com



**Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



**Sample Display Options**

