

PRODUCT ID: 46295
DOT LED Blank-Out Sign

MODEL
DOT2167AA-100DSH/100-240VAC

DIMENSIONS
21" H x 67" W x 5" D (est. 98.131 lbs)



CLASS
Class: DOT Series
Control Method: Switch (not included) or external relay.

CONSTRUCTION
Cabinet: Extruded aluminum cabinet with welded seams, NEMA 4X rated/IP66.
Hinged door with 1" silicone gasket, tool-less stainless-steel latches. 5.0" Deep.
Face Material: Replaceable 1/4" thick smoke-tinted polycarbonate (5109)
Faces: Single Faced Sign
Finish: Powdercoat Black
Integral Hood: Single piece 1/8" brake formed 6" deep aluminum hood
Mounting Channel: None

ELECTRICAL
Input Voltage: 100-240 VAC
Photodimming: (3) Redundant fail-safe photocells for auto photodimming
Power Supplies: Redundant
UL/cUL Listed: Listed for wet locations

MESSAGE
Illumination: Super bright direct view LEDs. Message blanks out when off.
Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
OPEN	Amber Narrow Angle LED	12.0"	0.130-0.064
CLOSED	Amber Narrow Angle LED	12.0"	0.162-0.067


NOTE: Above messages are independently controlled.

Signal-Tech
4985 Pittsburgh Ave.
Erie, PA 16509
Phone: (877) 547-9900
Fax: (814) 835-2300
Email: sales@signal-tech.com
Website: www.signal-tech.com



Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Sample Display Options

