## PRODUCT ID: 47216

Outdoor Blank-out LED Backlit Sign

#### MODEL

PHX718R-K133/12-24VDC



#### DIMENSIONS

7" H x 18" W x 2.5" D (est. 3.972 lbs)

### **CLASS**

Class: PHX Series

Control Method: Switch (not included) or external relay.

#### CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface Mounting Channel: None

#### **ELECTRICAL**

Flashing: Not Included Input Voltage: 12-24 VDC
UL/cUL Listed: Listed for wet locations

## **MESSAGE**

Color: Black opaque Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

#### **MESSAGE** LED/COLOR | HEIGHT | AMPS

DANGER LASER ON w/ Laser Symbol Red Wide Angle LED 4.125", 1.875" 1.307-0.653

NOTE: Above messages are independently controlled.

#### Signal-Tech

4985 Pittsburgh Ave. Erie. PA 16509 Phone: (877) 547-9900

Fax: (814) 835-2300


Email: sales@signal-tech.com Website: www.signal-tech.com



# **Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.





Frame Detail

2.5"

