PRODUCT ID: 47557

Outdoor Blank-out LED Backlit Sign

MODEL

PHX1418RG-L945/120-277VAC



DIMENSIONS

14" H x 18" W x 2.25" D (est. 7.962 lbs)

CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Cabinet: 1-piece, corrosion resistant, extruded all-weather frame, 2.25" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface **Mounting Channel**: None

ELECTRICAL

Flashing: Not Included Input Voltage: 120-277 VAC UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Black opaque Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
Red Indicator Dot WASH IN USE & Border	Red Wide Angle LED	5.25", 3.5", 2.0"	0.267-0.116
Green Indicator Dot ENTER & Border	Green Wide Angle LED	5.25", 3.5", 2.0"	0.413-0.179

NOTE: Above messages are independently controlled.

Signal-Tech

4985 Pittsburgh Ave. Erie, PA 16509 Phone: (877) 547-9900

Fax: (814) 835-2300


Email: sales@signal-tech.com Website: www.signal-tech.com



Proudly Made in the USA

Product View


NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Sample Display Options







Copyright (C) 2021 Signal-Tech