

**PRODUCT ID: 5132**  
Outdoor Blank-out LED Direct-view Sign

**MODEL**  
TCL1418R-193/120-277VAC



**DIMENSIONS**  
14" H x 18" W x 2.5" D (est. 6.812 lbs)

**CLASS**  
**CLASS:** TCL Series  
**Control Method:** Switch (not included) or external relay.

**CONSTRUCTION**  
**Back Construction:** 0.050" Lift-n-Shift Back  
**Cabinet:** 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.  
**Face Material:** 1/8" impact resistant, smoke-tinted acrylic (5109)  
**Faces:** Single Faced Sign  
**Finish:** Duranodic Bronze  
**Mounting Channel:** None

**ELECTRICAL**  
**Flashing:** Not Included  
**Input Voltage:** 120-277 VAC  
**Photodimming:** None  
**UL/cUL Listed:** Listed for wet locations

**MESSAGE**  
**Illumination:** Super bright direct view LEDs. Message blanks out when off.  
**Sign Messages:** See message table below

| MESSAGE      | LED/COLOR          | HEIGHT | AMPS        |
|--------------|--------------------|--------|-------------|
| LASER IN USE | Red Wide Angle LED | 3.5"   | 0.072-0.031 |


NOTE: Above messages are independently controlled.

**Signal-Tech**  
4985 Pittsburgh Ave.  
Erie, PA 16509  
Phone: (877) 547-9900  
Fax: (814) 835-2300  
Email: sales@signal-tech.com  
Website: www.signal-tech.com



**Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

