

MODEL

PHX732BRB-N406/120-277VAC

7" H x 32" W x 2.5" D (est. 7.264 lbs)

CLASS

Class: PHX Series Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: 1/8" thick, dark grey diffused acrylic Faces: Single Faced Sign Finish: Duranodic Bronze Graphic: Printed graphic applied to surface Mounting Channel: None

ELECTRICAL

Flashing: Factory setting 55fpm. Input Voltage: 120-277 VAC UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Black opaque Font: Swiss 721 Bold BT Illumination: Backlit with high intensity LEDs. Message blanks out when off Sign Messages: See message table below

MESSAGE

LOCKDOWN w/ Blue Indicator Dots Red, Blue Wide Angle LED 2.625", 5.0" 0.371-0.161

NOTE: Above messages are independently controlled.

Signal-Tech 4985 Pittsburgh Ave. Erie. PA 16509 Phone: (877) 547-9900 Fax: (814) 835-2300 Email: sales@signal-tech.com Website: www.signal-tech.com

Copyright (C) 2024 Signal-Tech