## **Product View** NOTE: Sign image may not exactly represent the finished product. For illustration purposes only. Outdoor LED Backlit Sign PHXF1212W-O521YK/120-277VAC 12" H x 12" W x 2.5" D (est. 5.878 lbs) CAUTION Control Method: Switch (not included) or external relay. Back Construction: 0.050" Lift-n-Shift Back Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. WATCH FOR Face Material: 1/8" thick, impact modified acrylic (0000) Graphic: Printed graphic applied to surface Mounting Channel: None 12 in Color: Translucent custom color (Yellow Translucent(R:255, G:242, B:0), Black Illumination: White high intensity LED backlit. Message always visible. **GATE ARM** LED/COLOR | HEIGHT | AMPS CAUTION WATCH FOR GATE ARM w/ Gate Hazard Symbol Yelow Translucent, Black Opaque, White Wride Ande LED 1.5", 1.25", 4.25" 0.217-0.094 -12 in -Frame Detail NOTE: Above messages are independently controlled. Signal-Tech

## Phone: (877) 547-9900 Fax: (814) 835-2300 Email: sales@signal-tech.com

Signal-Tech 4985 Pittsburgh Ave.

Erie. PA 16509

PRODUCT ID: 57154

MODEL

CLASS CLASS: PHXF Series

DIMENSIONS

CONSTRUCTION

Faces: Single Faced Sign Finish: Duranodic Bronze

ELECTRICAL Flashing: Not Included Input Voltage: 120-277 VAC UL/cUL Listed: Listed for wet locations

MESSAGE

Font: Swiss 721 Bold BT

Sign Messages: See message table below

MESSAGE

Opaque)