# PRODUCT ID: 57156

Outdoor LED Backlit Sign

### MODEL

PHXF1212W-O521YK/12-24VDC



## DIMENSIONS

12" H x 12" W x 2.5" D (est. 15.455 lbs)

# **CLASS**

**CLASS**: PHXF Series

Control Method: Switch (not included) or external relay.

# CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, impact modified acrylic (0000)

Faces: Single Faced Sign Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface Mounting Channel: None

### ELECTRICAL

Flashing: Not Included Input Voltage: 12-24 VDC

UL/cUL Listed: Listed for wet locations

#### **MESSAGE**

Color: Translucent custom color (Yellow Translucent(R:255, G:242, B:0), Black

Opaque)

Font: Swiss 721 Bold BT

Illumination: White high intensity LED backlit. Message always visible.

Sign Messages: See message table below

#### LED/COLOR | HEIGHT | AMPS MESSAGE

CAUTION WATCH FOR GATE ARM w/ Gate Hazard Symbol | Yelou Translucent, Black Opaque, White Mide Ande LED | 1.5", 1.25", 4.25" | 2.173-1.087

NOTE: Above messages are independently controlled.

#### Signal-Tech

4985 Pittsburgh Ave. Erie. PA 16509


Phone: (877) 547-9900 Fax: (814) 835-2300

Email: sales@signal-tech.com Website: www.signal-tech.com



# **Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

