PRODUCT ID: 5739

Outdoor Blank-out LED Direct-view Sign

MODEL

TCL3414GRGR-579/120-277VAC



DIMENSIONS

34" H x 14" W x 2.5" D (est. 13.793 lbs)

CLASS

CLASS: TCL Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" impact resistant, smoke-tinted acrylic (5109)

Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None

ELECTRICAL

Flashing: Not Included Input Voltage: 120-277 VAC Photodimming: None
UL/cUL Listed: Listed for wet locations

MESSAGE

Illumination: Super bright direct view LEDs. Message blanks out when off.

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
CLOSED w/ Down Left Arrow	Red Wide Angle LED	3.5"	0.051-0.022
OPEN w/ Down Left Arrow	Green Wide Angle LED	3.5"	0.067-0.029
CLOSED w/ Down Right Arrow	Red Wide Angle LED	3.5"	0.051-0.022
OPEN w/ Down Right Arrow	Green Wide Angle LED	3.5"	0.067-0.029

NOTE: Above messages are independently controlled.

Signal-Tech

4985 Pittsburgh Ave. Erie, PA 16509


Phone: (877) 547-9900 Fax: (814) 835-2300

Email: sales@signal-tech.com Website: www.signal-tech.com




Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



→ 2 1/2 in ←

Sample Display Options



Frame Detail

