PRODUCT ID: 57922

Internally Illuminated LED Traffic Sign

MODEL

STRI3030W-O772KA/120-277VAC



DIMENSIONS

30" H x 30" W x 6" D (est. 54.584 lbs)

CLASS

Class: STRi Class

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.125" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, triple hollow, extruded aluminum frame, 6"

Face Material: 1/8" thick, impact modified acrylic (0000)

Faces: Single Faced Sign

Finish: Black

Graphic: Printed graphic applied to surface **Mounting Channel**: None

ELECTRICAL

Flashing: Not Included Input Voltage: 120-277 VAC
UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Refer to message table (Black Opaque, Amber Translucent)

Illumination: Super bright direct view LEDs. Message blanks out when off.

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
Pinht Turning Arrow TURNING VEHICLES VIELD TO Padactrian Symbol	Rlark Orania, Amhar Translurant, White Wide Annie I FD	5 375" 2 875" 8 625" 11 5"	1 257.0 5/15

NOTE: Above messages are independently controlled.

Signal-Tech

4985 Pittsburgh Ave. Erie. PA 16509 Phone: (877) 547-9900

Fax: (814) 835-2300

Email: sales@signal-tech.com Website: www.signal-tech.com

Signal-Tech

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

