PRODUCT ID: 57944

Internally Illuminated LED Traffic Sign

MODEL

STRI3030W-0771KA/120-277VAC



DIMENSIONS

30" H x 30" W x 6" D (est. 40.629 lbs)

CLASS

Class: STRi Class

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.125" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, triple hollow, extruded aluminum frame, 6"

Face Material: 1/8" thick, impact modified acrylic (0000)

Faces: Single Faced Sign Finish: Black

Graphic: Printed graphic applied to surface **Mounting Channel**: None

ELECTRICAL

Flashing: Not Included Input Voltage: 120-277 VAC
UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Refer to message table (Black Opaque, Amber and Red Translucent)

Illumination: Backlit with high intensity LEDs Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
Left Turning Arrow TURNING VEHICLES VIELD TO Pedestrian Symbol	Rlack Onanue, Amber and Red Translucent, White Wide Angle LFD	5.375" 2.875" 8.625" 11.5"	1.257-0.545

NOTE: Above messages are independently controlled.

Signal-Tech

4985 Pittsburgh Ave. Erie. PA 16509 Phone: (877) 547-9900

Fax: (814) 835-2300 Email: sales@signal-tech.com Website: www.signal-tech.com



Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

