PRODUCT ID: 68765

DOT LED Blank-Out Sign

MODEL

DOT4129RW-D601/9-24VDC



DIMENSIONS

41" H x 29" W x 6.5" D (est. 66.249 lbs)

CLASS

Class: DOT Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Cabinet: Extruded aluminum cabinet with welded seams, up to NEMA 4X rated/IP66. Hinged door with silicone gasket, tool-less stainless-steel latches. 6.5"

Face Material: 1/8" impact resistant, smoke-tinted acrylic (5109)
Faces: Single Faced Sign
Finish: Powdercoat Black

ELECTRICAL

Input Voltage: 9-24 VDC
Photodimming: IR photocells for auto photodimming
Power Supplies: No Redundancy
UL/cUL Listed: Listed for wet locations

MESSAGE

Illumination: Super bright direct view LEDs. Message blanks out when off.

Sign Messages: See message table below

LED/COLOR | HEIGHT | AMPS **MESSAGE**

No Left Turn Symbol w/TRAIN Red, White Narrow Angle LED 21.0", 6.0" 5.796-2.173

NOTE: Above messages are independently controlled.

Signal-Tech

4985 Pittsburgh Ave. Erie, PA 16509 Phone: (877) 547-9900

Fax: (814) 835-2300


Email: sales@signal-tech.com Website: www.signal-tech.com



03262024 | EMC

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

